



BlackGuard PVC Coated Expansion Deflection Coupling XD

BlackGuard PVC coated XD Expansion/Deflection Couplings are used with PVC coated rigid conduit to accommodate axial expansion, angular misalignment and parallel misalignment. They feature an internal bonding jumper. PVC coating and internal urethane coating provide for superior corrosion protection. Electrical continuity is maintained across assembled joints.

Features

- Axial expansion or contraction up to 3/4"
- Angular misalignment in any direction to 30*
- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- XD in 10 trade sized from 1" through 5"
- Sealing sleeves



Part Number	Description	A (dia)	B (length)
PF-XD-100	1" EXPANSION/DEFLECTION COUPLING	7.00	3.94
PF-XD-125	1-1/4" EXPANSION/DEFLECTION COUPLING	7.375	4.25
PF-XD-150	1-1/2" EXPANSION/DEFLECTION COUPLING	7.25	4.5
PF-XD-200	2" EXPANSION/DEFLECTION COUPLING	7.25	4.94
PF-XD-250	2-1/2" EXPANSION/DEFLECTION COUPLING	7.5	5.3125
PF-XD-300	3" EXPANSION/DEFLECTION COUPLING	7.625	5.94
PF-XD-350	3-1/2" EXPANSION/DEFLECTION COUPLING	7.75	6.5
PF-XD-400	4" EXPANSION/DEFLECTION COUPLING	7.875	6.94
PF-XD-500	5" EXPANSION/DEFLECTION COUPLING	7.75	8