



## BlackGuard PVC Coated Conduit Couplings

### Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil

### Specifications

- Manufactured to UL6 and ANSI C80.1 Standards
- PVC as primary corrosion protection
- UL Listed (E100475)



GRC PART NUMBER	SIZE	METRIC	Metal	per Inch	WEIGHT PER 100	Box Qty	ALUMINUM PART NUMBER
PVC-CG-050	1/2"	16	1.5	14	19	100	PVC-AC-050
PVC-CG-075	3/4"	21	1.532	14	32	90	PVC-AC-075
PVC-CG-100	1"	27	1.906	11.5	40	75	PVC-AC-100
PVC-CG-125	1-1/4"	35	1.906	11.5	50	42	PVC-AC-125
PVC-CG-150	1-1/2"	41	1.906	11.5	69	38	PVC-AC-150
PVC-CG-200	2"	53	1.937	11.5	93	30	PVC-AC-200
PVC-CG-250	2-1/2"	63	2.878	8	123	17	PVC-AC-250
PVC-CG-300	3"	78	3.031	8	217	14	PVC-AC-300
PVC-CG-350	3-1/2"	91	3.094	8	422	11	PVC-AC-350
PVC-CG-400	4"	103	3.188	8	391	11	PVC-AC-400
PVC-CG-500	5"	129	3.374	8	550	8	PVC-AC-500
PVC-CG-600	6"	155	3.437	8	884	5	PVC-AC-600