



## BlackGuard PVC Coated Malleable Fittings - 90° Female-Female

**BlackGuard** PVC coated EL style elbows used where a very tight radius elbow is required. They are available with female & male threaded connections. Female threaded hubs supplied with a sealing sleeve. Male ends supplied with a sealing form.

### Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" through 2-1/2"

### Specifications

- National Electric Code/CEC 1/2", 3/4", 1" Class I, Division 1 & 2, Groups A, B, C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups F, G Class III
- All sizes Class I, Division 1 & 2, Groups C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups F, G Class III
- UL Standard 886
- CSA Standard: C22.2 No.18



PART NUMBER	SIZE	A	WEIGHT PER 100	ALUMINUM PART NUMBER
PVC-FIT-EL050FF	1/2"	2.03	70	PVC-FIT-EL050FFA
PVC-FIT-EL075FF	3/4"	2.50	90	PVC-FIT-EL075FFA
PVC-FIT-EL100FF	1"	3.00	120	PVC-FIT-EL100FFA
PVC-FIT-EL125FF	1-1/4"	3.50	240	PVC-FIT-EL125FFA
PVC-FIT-EL150FF	1-1/2"	5.50	300	PVC-FIT-EL150FFA
PVC-FIT-EL200FF	2"	7.00	600	PVC-FIT-EL200FFA
PVC-FIT-EL250FF	2-1/2"	8.44	790	PVC-FIT-EL250FFA