



BlackGuard PVC Coated Malleable Fittings - 90° Male-Male

BlackGuard PVC coated EL style elbows used where a very tight radius elbow is required. They are available with female & male threaded connections. Female threaded hubs supplied with a sealing sleeve. Male ends supplied with a sealing form.

Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" through 4"

Specifications

- National Electric Code/CEC 1/2", 3/4", 1" Class I, Division 1 & 2, Groups A, B, C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups F, G Class III
- All sizes Class I, Division 1 & 2, Groups C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups F, G Class III
- UL Standard 886
- CSA Standard: C22.2 No.18



PART NUMBER	SIZE	A	WEIGHT PER 100	ALUMINUM PART NUMBER
PVC-FIT-EL050MM	1/2"	1.44	30	PVC-FIT-EL050MMA
PVC-FIT-EL075MM	3/4"	1.63	50	PVC-FIT-EL075MMA
PVC-FIT-EL100MM	1"	1.88	70	PVC-FIT-EL100MMA