

BlackGuard PVC Coated Sealing Fittings – EZS Male-Female Hubs w/Drain

BlackGuard PVC coated Sealing Fittings used in hazardous locations to prevent flame and gas from continuing to travel through the conduit system. PVC coating provides corrosion protection. A sealing compound should be used on the interior after wiring. Compound supplied by the original fitting manufacturer.

Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" through 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2". For sizes 2-1/2" - 6", the length of the sleeve extension(s) shall be at least 2".
- Sealing sleeve provided on plug hub (patching compound on top of plug)
- Mating sealing forms provided on all caps
- Sealing sleeves on all conduit openings

Specifications

- EYS-1-3, 11-31,16-36, 116-316
- Class groups A, B, C, D
- Class II, groups E, F, G
- Class III
- EYS-41-101, 416-1016
- EYSX-11-81
- EYD-11-101, 116-1016
- EYDX-11-81
- Class groups B, C, D
- Class II, Groups E, F, G
- Class III
- EYS-29, 4-014,46-0146
- EZS-1-8, 16-86
- EYSX-9-10
- EYD-1-10, 16-106
- EZD-10-60
- Class groups C, D
- Class II, Groups E, F, G
- Class III
- UL Standard 886
- CSA Standard: C22.2 No.30

PART NUMBER	SIZE	A	B	C	WEIGHT PER 100
PVC-FIT-EZSMF050	1/2"	5.19	3.71	2.58	200
PVC-FIT-EZSMF075	3/4"	5.69	3.71	2.58	240
PVC-FIT-EZSMF100	1"	6.94	4.05	3.08	300
PVC-FIT-EZSMF125	1-1/4"	7.56	4.49	3.08	400
PVC-FIT-EZSMF150	1-1/2"	8.19	4.64	3.33	460
PVC-FIT-EZSMF200	2"	11.06	5.49	5.27	690
PVC-FIT-EZSMF250	2-1/2"	11.94	5.92	5.27	920
PVC-FIT-EZSMF300	3"	12.63	6.58	5.96	870