

## BlackGuard PVC Coated Junction Boxes for Hazardous Locations - GUAT


BlackGuard PVC coated GUA style fittings are available in a variety of shapes and dimensions. GUA style boxes are used in hazardous locations. All GUA style boxes are supplied PVC Coated with PVC Coated covers and a seal between the coating of the boxes and the coating of the covers.

### Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" through 2"
- Sealing sleeves extender 1 pipe diameter or 2 inches, whichever is greater, beyond all female openings

### Specifications

- National Electrical Code:
  - Class I, Div 1&2, Groups C,D
  - Class II, Div 1, Groups E,F,G
  - Class II, Div 2, Groups F,G
  - Class III • UL Standard 886
- UL Standard 886
- ANSI Standard C-33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4



PART NUMBER	SIZE	Cover Opening	A	B	C	D	WEIGHT PER 100	ALUMINUM PART NUMBER
PVC-FIT-GUAT05014	1/2"	2"	2.58	1.85	1.75	0.67	200	
PVC-FIT-GUAT05016	1/2"	3"	3.58	2.04	1.88	0.67	280	PVC-FIT-GUAT05016
PVC-FIT-GUAT07524	3/4"	2"	2.58	2.04	2.00	0.79	220	
PVC-FIT-GUAT07526	3/4"	3"	3.58	2.04	1.88	0.79	350	PVC-FIT-GUAT07526
PVC-FIT-GUAT10036	1"	3"	3.58	2.35	2.19	0.92	320	PVC-FIT-GUAT10036
PVC-FIT-GUAT12547	1-1/4"	3-5/8"	4.33	2.73	2.75	1.13	570	PVC-FIT-GUAT12547
PVC-FIT-GUAT15059	1-1/2"	5"	5.83	3.85	3.75	1.32	910	PVC-FIT-GUAT15059
PVC-FIT-GUAT20069	2"	5"	5.83	4.10	4.00	1.60	100	PVC-FIT-GUAT20069