

## BlackGuard PVC Coated Junction Boxes for Hazardous Locations - GUAW

**BlackGuard** PVC coated GUA style fittings are available in a variety of shapes and dimensions. GUA style boxes are used in hazardous locations. All GUA style boxes are supplied PVC Coated with PVC Coated covers and a seal between the coating of the boxes and the coating of the covers.

### Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" through 2"
- Sealing sleeves extender 1 pipe diameter or 2 inches, whichever is greater, beyond all female openings

### Specifications

- National Electrical Code:
  - Class I, Div 1&2, Groups C,D
  - Class II, Div 1, Groups E,F,G
  - Class II, Div 2, Groups F,G
  - Class III • UL Standard 886
- ANSI Standard C-33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4



PART NUMBER	SIZE	Cover Opening	A	B	C	D	WEIGHT PER 100
PVC-FIT-GUAW05014	1/2"	2"	2.58	1.85	1.75	0.67	200
PVC-FIT-GUAW05016	1/2"	3"	3.58	2.04	1.88	0.67	200
PVC-FIT-GUAW07524	3/4"	2"	2.58	2.04	2.00	0.79	300
PVC-FIT-GUAW07526	3/4"	3"	2.58	2.04	1.88	0.79	300