

BlackGuard PVC Coated Form 8 LR Fittings

BlackGuard offers a complete line of Form 8 and Form 7 PVC coated conduit bodies. All fittings supplied with PVC coated cast iron covers. The sleeved threaded ends offer complete protection against corrosion while maintaining full ground continuity throughout the installed system.

Features


- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Specialized corrosion resistant coating provided on threads
- Sizes available are 1/2" to 4"
- Fittings supplied with plastic encapsulated stainless steel screws
- Sealing sleeves extender 1 pipe diameter or 2 inches, whichever is greater, beyond all female openings.




Specifications

• UL Standard 514B

• CSA Standard: C22.2 No. 18





PART NUMBER	SIZE	METRIC	A	В	С	D	E	WEIGHT PER 100
PVC-FIT-LR0508	1/2"	16	5.48	1.48	2.20	1.00	3.31	140
PVC-FIT-LR0758	3/4"	21	6.35	1.73	2.35	1.19	3.94	210
PVC-FIT-LR1008	1"	27	7.51	1.98	2.67	1.38	4.56	260
PVC-FIT-LR1258	1-1/4"	35	8.82	2.42	3.20	1.75	5.31	450
PVC-FIT-LR1508	1-1/2"	41	10.67	2.82	4.04	2.13	6.50	620
PVC-FIT-LR2008	2"	53	13.04	3.60	5.04	3.00	8.56	1070
PVC-FIT-LR2508	2-1/2"	63	15.98	4.48	6.73	4.25	10.88	1770
PVC-FIT-LR3008	3"	78	15.98	4.85	6.73	4.25	10.88	1800
PVC-FIT-LR3508	3-1/2"	91	14.73	4.92	6.98	4.50	10.25	2100
PVC-FIT-LR4008	4"	103	14.73	5.42	6.98	4.50	10.25	2400