



## BlackGuard PVC Coated Liquidtight Connectors – 45°

BlackGuard PVC coated liquidtight connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector is seized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.


### Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Sizes available are 1/2" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2". For sizes 2-1/2" - 6", the length of the sleeve extension(s) shall be at least 2".
- Available in straight, 45 degree or 90 degree body configurations



### Specifications

- UL Standard 514B
- CSA Standard: C22.2 No. 18



PART NUMBER	SIZE	A	B	C	WEIGHT PER 100
PVC-FIT-LT037545	3/8"	1.24	1.94	0.56	30
PVC-FIT-LT05045	1/2"	1.46	2.38	0.56	30
PVC-FIT-LT07545	3/4"	1.74	2.88	0.56	40
PVC-FIT-LT10045	1"	1.96	3.25	0.75	50
PVC-FIT-LT12545	1-1/4"	2.36	4.00	0.81	150
PVC-FIT-LT15045	1-1/2"	2.80	4.88	0.81	120
PVC-FIT-LT20045	2"	3.33	5.88	0.88	200
PVC-FIT-LT25045	2-1/2"	3.83	6.25	1.00	300
PVC-FIT-LT30045	3"	4.58	6.25	1.00	420
PVC-FIT-LT40045	4"	5.58	6.63	1.13	620