




BlackGuard PVC Coated Liquidtight Connectors – Straight w/Ground

BlackGuard PVC coated liquidtight connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector is seized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Sizes available are 1/2" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2". For sizes 2-1/2"- 6", the length of the sleeve extension(s) shall be at least 2".
- Available in straight, 45 degree or 90 degree body configurations



Specifications

- UL Standard 514B
- CSA Standard: C22.2 No. 18

PART NUMBER	SIZE	A	B	C	WEIGHT PER 100	ALUMINUM PART NUMBER
PVC-FIT-LT0375G	3/8"	1.24	1.88	0.56	20	
PVC-FIT-LT050G	1/2"	1.46	2.06	0.56	20	PVC-FIT-LT050GA
PVC-FIT-LT075G	3/4"	1.74	2.38	0.56	30	PVC-FIT-LT075GA
PVC-FIT-LT100G	1"	1.96	3.06	0.75	40	PVC-FIT-LT100GA
PVC-FIT-LT125G	1-1/4"	2.33	3.75	0.81	80	PVC-FIT-LT125GA
PVC-FIT-LT150G	1-1/2"	3.33	4.19	0.81	90	PVC-FIT-LT150GA
PVC-FIT-LT200G	2"	3.89	5.06	0.88	170	PVC-FIT-LT200GA
PVC-FIT-LT250G	2-1/2"	4.52	6.13	1.00	300	PVC-FIT-LT250GA
PVC-FIT-LT300G	3"	5.27	6.25	1.00	420	PVC-FIT-LT300GA
PVC-FIT-LT400G	4"	6.21	6.50	1.13	620	PVC-FIT-LT400GA