



BlackGuard PVC Coated Liquidtight Connectors - Straight


BlackGuard PVC coated liquidtight connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector seized specifically to tighten around PVC conduit. Pulling compound recommended for ease of installation. Fittings provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Sizes available are 1/2" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2". For sizes 2-1/2"- 6", the length of the sleeve extension(s) shall be at least 2".
- Available in straight, 45 degree or 90 degree body configurations

Specifications

- UL Standard 514B
- CSA Standard: C22.2 No. 18



PART NUMBER	SIZE	A	B	C	WEIGHT PER 100	ALUMINUM PART NUMBER
PVC-FIT-LT0375	3/8"	1.24	1.88	0.56	20	PVC-FIT-LT0375A
PVC-FIT-LT050	1/2"	1.46	2.06	0.56	20	PVC-FIT-LT050A
PVC-FIT-LT075	3/4"	1.74	2.38	0.56	30	PVC-FIT-LT075A
PVC-FIT-LT100	1"	1.96	3.06	0.75	40	PVC-FIT-LT100A
PVC-FIT-LT125	1-1/4"	2.36	3.75	0.81	80	PVC-FIT-LT125A
PVC-FIT-LT150	1-1/2"	2.80	4.19	0.81	90	PVC-FIT-LT150A
PVC-FIT-LT200	2"	3.33	5.06	0.88	170	PVC-FIT-LT200A
PVC-FIT-LT250	2-1/2"	3.83	6.13	1.00	300	PVC-FIT-LT250A
PVC-FIT-LT300	3"	4.58	6.25	1.00	420	PVC-FIT-LT300A
PVC-FIT-LT400	4"	5.58	6.50	1.13	620	PVC-FIT-LT400A