

BlackGuard PVC Coated Reducing Couplings

BlackGuard PVC coated reducing couplings used to join conduit and fittings of different sizes. They are provided with different size sleeves to match the fittings thread sizes.

Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" to 6"
- Sealing sleeves extender 1 pipe diameter or 2 inches, whichever is greater, beyond all female openings



Specifications

- National Electric Code/CEC Class I, Division 1 & 2, Groups A, B, C, D Class II, Groups E, F, G Class III
- UL Standard 886
- CSA Standard: C22.2 No.18

PART NUMBER	SIZE	WEIGHT PER 100	ALUMINUM PART NUMBER
PVC-FIT-RC075050	3/4" - 1/2"	20	PVC-FIT-RC075050A
PVC-FIT-RC100050	1" - 1/2"	70	PVC-FIT-RC100050A
PVC-FIT-RC100075	1" - 3/4"	50	PVC-FIT-RC100075A
PVC-FIT-RC125075	1-1/4" - 3/4"	100	PVC-FIT-RC125075A
PVC-FIT-RC125100	1-1/4" - 1"	80	PVC-FIT-RC125100A
PVC-FIT-RC150075	1-1/2" - 3/4"	140	PVC-FIT-RC150075A
PVC-FIT-RC150100	1-1/2" - 1"	120	PVC-FIT-RC150100A
PVC-FIT-RC150125	1-1/2" - 1-1/4"	130	PVC-FIT-RC150125A
PVC-FIT-RC200075	2" - 3/4"	150	PVC-FIT-RC200075A
PVC-FIT-RC200100	2" - 1"	230	PVC-FIT-RC200100A
PVC-FIT-RC200125	2" - 1-1/4"	260	PVC-FIT-RC200125A
PVC-FIT-RC200150	2" - 1-1/2"	280	PVC-FIT-RC200150A
PVC-FIT-RC250150	2-1/2" - 1-1/2"	320	
PVC-FIT-RC300200	3" - 2"	370	PVC-FIT-RC300200A
PVC-FIT-RC350250	3-1/2" - 2-1/2"	460	
PVC-FIT-RC400300	4" - 3"	590	
PVC-FIT-RC500400	5" - 4"	74	