



## BlackGuard PVC Coated Split Couplings

**BlackGuard** PVC coated split couplings used to connect two pieces of conduit where the conduit cannot be turned. BlackGuard split couplings are PVC coated for corrosion protection.

### Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- Sizes available are 1/2" to 6"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"-2".  
For sizes 2-1/2" -6", the length of the sleeve extension(s) shall be at least 2".
- Stainless steel hardware included



### Specifications

- UL Standard 514B
- CSA Standard: C22.2 No.18

PART NUMBER	SIZE	WEIGHT PER 100
PVC-FIT-SC050	1/2"	20
PVC-FIT-SC075	3/4"	30
PVC-FIT-SC100	1"	40
PVC-FIT-SC125	1-1/4"	60
PVC-FIT-SC150	1-1/2"	70
PVC-FIT-SC200	2"	100
PVC-FIT-SC250	2-1/2"	230
PVC-FIT-SC300	3"	300
PVC-FIT-SC350	3-1/2"	380
PVC-FIT-SC400	4"	410
PVC-FIT-SC500	5"	600
PVC-FIT-SC600	6"	860