




BlackGuard PVC Coated Hubs – STG w/Ground

BlackGuard PVC coated STG style hubs with grounding used to terminate conduit runs through the wall of a sheet metal electrical enclosure. They are available with or without grounding lug.

Features

- Exterior dark grey PVC coating with a minimum thickness of 40 mil
- Interior Urethane coating with a minimum thickness of 2 mil
- STG available in 12 trade sizes from 1/2" through 6"
- Sealing sleeves on conduit side of hub
- Molded PVC gasket seals flush with enclosure wall
- Neoprene O-ring gasket provides additional seal
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2" - 2". For sizes 2-1/2" - 6", the length of the sleeve extension(s) shall be at least 2".



Specifications

- UL Standard 514B
- CSA Standard: C22.2 No. 18

| PART NUMBER | SIZE | A | B | C | WEIGHT PER 100 (LBS) | ALUMINUM PART NUMBER |
|-----------------|--------|------|------|------|----------------------|----------------------|
| PVC-FIT-STG050G | 1/2" | 1.84 | 2.00 | 1.31 | 20 | PVC-FIT-STG050GA |
| PVC-FIT-STG075G | 3/4" | 2.22 | 2.25 | 1.66 | 30 | PVC-FIT-STG075GA |
| PVC-FIT-STG100G | 1" | 2.66 | 2.50 | 2.03 | 40 | PVC-FIT-STG100GA |
| PVC-FIT-STG125G | 1-1/4" | 2.94 | 3.25 | 2.28 | 40 | PVC-FIT-STG125GA |
| PVC-FIT-STG150G | 1-1/2" | 3.19 | 3.50 | 2.53 | 60 | PVC-FIT-STG150GA |
| PVC-FIT-STG200G | 2" | 3.75 | 4.25 | 3.09 | 120 | PVC-FIT-STG200GA |
| PVC-FIT-STG250G | 2-1/2" | 4.22 | 4.75 | 3.28 | 150 | PVC-FIT-STG250GA |
| PVC-FIT-STG300G | 3" | 4.31 | 5.25 | 3.38 | 210 | PVC-FIT-STG300GA |
| PVC-FIT-STG350G | 3-1/2" | 4.38 | 5.50 | 3.44 | 300 | PVC-FIT-STG350GA |
| PVC-FIT-STG400G | 4" | 4.44 | 6.25 | 3.50 | 350 | PVC-FIT-STG400GA |
| PVC-FIT-STG500G | 5" | 4.94 | 7.50 | 4.00 | 540 | |
| PVC-FIT-STG600G | 6" | 5.00 | 8.50 | 4.00 | 690 | |